

# Granville Jack Oil

500ml

## PRODUCT DESCRIPTION

Granville Jack Oil is a fully inhibited hydraulic oil developed specifically for use in hydraulic trolley and bottle jacks. Jack Oil has been specifically formulated to alleviate slow system response and sponginess.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ISO: 32 & VG22

## PRODUCT BENEFITS

\* Prevents slow response & sponginess

## PRODUCT USAGE

Developed specifically for use for use in hydraulic trolley and bottle jacks.

## DIRECTIONS FOR USE

As per the manufacturers recommendations

## STORAGE INSTRUCTIONS

Store sealed in a cool, dry place

## SHELF LIFE

5 years from date of manufacture.

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
500ml	0177	5020618001775



# Granville Jack Oil

500ml

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s	28.8	35.2	32.57
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s			5.54
Density	ASTM D792	@ 15°C			0.871

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

